

CHEMFIX CH200

Page: 1
Compilation date: 10/05/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CHEMFIX CH200

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: A Chemical anchoring application

1.3. Details of the supplier of the safety data sheet

Company name: Chemfix Products Limited

Mill Street East Dewsbury

West Yorkshire

WF12 9BQ

United Kingdom

Tel: +44 (0)1924 453886

Fax: +44 (0)1924 458995

Email: sds@chemfix.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1924 431679

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H335; Eye Irrit. 2: H319; Skin Sens. 1: H317

Most important adverse effects: May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation.

2.2. Label elements

Label elements:Hazard statements:H317: May cause an allergic skin reaction.H319: Causes serious eye irritation.H335: May cause respiratory irritation.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

CHEMFIX CH200

Page: 2

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/soap and water.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHYLENE DIMETHACRYLATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent	
202-617-2	97-90-5	-	STOT SE 3: H335; Skin Sens. 1: H317	10-20%	
METHACRYLIC ACID, MONOESTER WITH PROPANE-1,2-DIOL - REACH registered number(s): 01-2119490226-37					
248-666-3	27813-02-1	-	Eye Irrit. 2: H319; Skin Sens. 1: H317	3-10%	
DIBENZOYL PEROXIDE - REACH registered number(s): 01-2119511472-50-XXXX					
202-327-6	94-36-0	-	Self-react. B: H241; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; Skin Sens. 1: H317	1-3%	
		N-2-01	Irrit. 2: H319; Skin Sens. 1: H317		

 254-075-1
 38668-48-3
 Acute Tox. 2: H300; Aquatic Chronic 3: H412; Eye Dam. 1: H318
 <1%</th>

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

CHEMFIX CH200

Page: 3

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eves.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

CHEMFIX CH200

			GHEMI IX OH	200	Page: 4	
7.3. Specific er	nd use(s)				-	
Specific end use(s): Building and construction work (SU19).						
Section 8: Exposure controls/personal protection						
Section 8: Expo	osure controls	s/persona	I protection			
8.1. Control pa	arameters					
	n ave die nte .					
Hazardous ir	-					
DIBENZOYL	PEROXIDE					
Workplace e	xposure limits	:		Respirable dust		
State	8 hour T	WA	15 min. STEL	8 hour TWA	15 min. STEL	
UK		5 mg/m3	-	-	-	
DNEL/PNEC V	alues					
	DNEL / PNEC	No doto o	voilabla			
8.2. Exposure						
-	-	Ensure there is sufficient ventilation of the area.				
Respiratory protection:		Self-contained breathing apparatus must be available in case of emergency. Breathing				
		protection	is required in inadequately	y ventilated places. Gas/vap	oour filter, type A: organic	
		vapours (EN141).				
Hand protection:		Protective gloves. Nitrile gloves. Viton gloves. EN 374 Recommended thickness of				
		material >	0.4 mm. Breakthrough tim	e of the glove material > 8 h	ours. As the product is a	
		preperation of several substances, the resistance of the glove material can not be				
calcul		calculated	calculated in advance and has therefore to be checked prior to the application.			
Eye protection:		Safety glasses. Ensure eye bath is to hand.				
Skin protection: Protective clothing.						
Section 9: Phys	sical and cher	nical prop	perties			
9.1. Informatio	on on basic phy	vsical and o	chemical properties			
	State:	Paste				
		Various				
	Odour:	Character	istic odour			
	Oxidising:					
Solul	bility in water:					
Relative density: 1.7				voo	; g/l: 114	
9.2. Other info						
		Solid ouer	ongion clossified on the	flammable according to re-	ulto from Toot N 1 toot	
othe	a mormation:			-flammable according to res	SUILS ITOTTI TEST IN. I TEST	
			r readily combustible solid	э.		

CHEMFIX CH200

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHYLENE DIMETHACRYLATE

IPR	RAT	LD50	2800	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	3300	mg/kg

DIBENZOYL PEROXIDE

ORL	RAT	LD50	2000	mg/kg
VAPOURS	RAT	LD50	24.3	mg/kg

1,1'-(P-TOLYLIMINO)DIPROPAN-2-OL

ORAL RAT LD50 25 mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation DRM		Hazardous: calculated

Page: 5

CHEMFIX CH200

			Page:	
STOT-single exposure		INH	Hazardous: calculated	
Symptoms / routes of exposu	re			
Skin contact:	There may	be irritation and red	ness at the site of contact.	
Eye contact: There may be irritation and redness. The eyes may water profusely.				
Ingestion: There may be soreness and redness of the mouth and throat.				
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may			
	cause cou	ghing or wheezing.		
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.			
ction 12: Ecological inform	nation			

12.1. Toxicity

Ecotoxicity values: Catalyst Comp B

Species	Test	Value	Units
FISH	96H LC50	>500	mg/l
Daphnia magna	48H EC50	>500	mg/l
ALGAE	72H IC50	150	mg/l

Hazardous ingredients:

DIBENZOYL PEROXIDE

ALGAE	72H ErC50	0.0711	mg/l
Daphnia magna	48H EC50	0.110	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	0.0602	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

CHEMFIX CH200

Page: 7

13.1. Waste treatment methods Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. Waste code number: 08 04 12 Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes. NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal. Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	Active Oxygen Content of Catalyst Component 0.99%
	* indicates text in the SDS which has changed since the last revision.
	MAL Code: 1-5
Phrases used in s.2 and s.3:	H241: Heating may cause a fire or explosion.
	H300: Fatal if swallowed.
	H317: May cause an allergic skin reaction.
	H318: Causes serious eye damage.
	H319: Causes serious eye irritation.
	H335: May cause respiratory irritation.
	H400: Very toxic to aquatic life.
	H410: Very toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.